


REMARKS

The above amendments to the specification are in response to a typographical error by the translator in translating the PCT application into English. To the extent that the errors are in the mathematical formulae, which are really neither "German" nor "English," the propriety of these amendments should be obvious. The Examiner should note that the amended formulas are now in accord with the original published PCT application WO 00/76057 at page 5, lines 17 and 19. A marked copy of that page is attached.

These amendments do not introduce new subject matter.

Respectfully submitted,



Stephen L. Grant
Reg. No. 33,390
Hahn Loeser & Parks LLP
1225 W. Market St.
Akron, OH 44313
330-864-5550
Fax 330-864-7986
Email: slgrant@hahnlaw.com
Customer No. 021324

CLEAN COPY OF AMENDED PARAGRAPHS.

[0026] Closure of the switching means S_x therefore causes halving of the inductance which is crucial in terms of the oscillator frequency. The quality of the pairs of coils L_1 and L_2 is equal to the quality of the individual coil. If it is considered that the following approximately applies for the oscillator frequency:

$$f_0 = 1 / \sqrt{L},$$

the following relationship is found for the lower limit frequency $f_{0,\min}$ and for the upper limit frequency $f_{0,\max}$ for the frequency tuning range:

$$f_{0,\max} = \sqrt{2} \cdot f_{0,\min}$$

[0027] The following similarly applies for the general case of coils which are not necessarily the same:

$$f_{0,\max} = \sqrt{(1 + L_1 / L_2)} \cdot f_{0,\min}$$